By Rich P Page 1 of 9



Driver's side. The foglight bulb's size is H3 at 55W. Take note that the passenger's side is the exact mirror image of the driver's side. Simply follow the same procedures for the driver's side.

These were performed on a 2001.5 Volkswagen Passat 1.8T. It may also apply to other model years and trims.

WARNING: Avoid touching the glass of the halogen bulb with bare hands. Use alcohol to clean off any contaminants.

By Rich P Page 2 of 9



First step is to take the grill out. With your thumb and index finger on each clip, squeeze in to release and pull out.

These were performed on a 2001.5 Volkswagen Passat 1.8T. It may also apply to other model years and trims.

WARNING: Avoid touching the glass of the halogen bulb with bare hands. Use alcohol to clean off any contaminants.

By Rich P Page 3 of 9



Here's what it looks like without the grill.

These were performed on a 2001.5 Volkswagen Passat 1.8T. It may also apply to other model years and trims.

WARNING: Avoid touching the glass of the halogen bulb with bare hands. Use alcohol to clean off any contaminants.

By Rich P Page 4 of 9



Unscrew the foglight's housing.

These were performed on a 2001.5 Volkswagen Passat 1.8T. It may also apply to other model years and trims.

**WARNING:** Avoid touching the glass of the halogen bulb with bare hands. Use alcohol to clean off any contaminants.

By Rich P Page 5 of 9



You can continue without disconnecting the wiring, or you can disconnect it by pressing down at the point shown by the arrow and pulling out the connector. Open the housing by twisting the top portion counter-clockwise.

These were performed on a 2001.5 Volkswagen Passat 1.8T. It may also apply to other model years and trims.

WARNING: Avoid touching the glass of the halogen bulb with bare hands. Use alcohol to clean off any contaminants.

By Rich P Page 6 of 9



Disconnect the positive terminal by pulling them apart.

These were performed on a 2001.5 Volkswagen Passat 1.8T. It may also apply to other model years and trims.

WARNING: Avoid touching the glass of the halogen bulb with bare hands. Use alcohol to clean off any contaminants.

By Rich P Page 7 of 9



Release the clips that hold the bulb in place. Push down then out on each.

These were performed on a 2001.5 Volkswagen Passat 1.8T. It may also apply to other model years and trims.

WARNING: Avoid touching the glass of the halogen bulb with bare hands. Use alcohol to clean off any contaminants.

By Rich P Page 8 of 9



The bulb is now ready to be pulled out.

These were performed on a 2001.5 Volkswagen Passat 1.8T. It may also apply to other model years and trims.

**WARNING:** Avoid touching the glass of the halogen bulb with bare hands. Use alcohol to clean off any contaminants.

By Rich P Page 9 of 9



Remove the old bulb and secure the new one.

Go through each step in reverse order to put everything back to normal. The passenger's side is the exact mirror image of the driver's side. Follow the same steps for the passenger's side.

These were performed on a 2001.5 Volkswagen Passat 1.8T. It may also apply to other model years and trims.

**WARNING:** Avoid touching the glass of the halogen bulb with bare hands. Use alcohol to clean off any contaminants.